

DESCRIPTION

The AluLight is an aluminum, nonrated access panel suitable for any openings in interior or exterior walls. The 20 ga /1mm aluminum door provides sufficient strength for any application.

The door is equipped with fixed hinges and suitable for left- or right-hand operation.

It consists of welded aluminum frame and an aluminum door leaf supplied with a screwdriver operated cam latch or round cylinder lock with key.

SPECIFICATION

INSULATION: 3/4" polystyrene

GASKETING: Extruded santoprene

CAPABILITIES: This panel can be mounted into any kind of walls. Simple installation due to its structure and low weight are advantages of this lightweight panel.

ADVANTAGES

- Superior engineering & innovative design
- Fast delivery
- Quick and easy installation
- Economical solution
- Universal door

OPTIONS (at additional cost)

- Round Cylinder Lock with Key (Z)
- Screwdriver operated cam latch (SD)

For a complete list of options visit www.AccessDoorsAndPanels.com





To view Pricing and Additional Product Info.

SUBMITTAL/TECHNICAL DATA SHEET






■ DIMENSIONS AND APPEARANCE

>> CLICK TO VIEW ADDITIONAL DETAILS AND PRICING <<

STANDARD SIZES:

SYSTEM ALULIGHT	DIMENSIONS				
CODE	A inch mm	A inch mm			
L305305AL	12" 305	12" 305			
L406406AL	16" 406	16" 406			
L508508AL	20" 508	20" 508			
L610610AL	24" 610	24" 610			

ROUGH OPENING IS DOOR SIZE + " (9 MM)



PROJECT DATA

Custom Sizes Available - Fast!

PROJECT NAME :	QTY	W	Н	OPTIONS	
ARCHITECT:					
DEALER:					
CONTRACTOR:					
LOCATION:	SPECIAL INSTRUCTIONS:				
DATE:					
TAGGING INSTRUCTIONS:	SUBMITTAL APPROVAL : (signature or stamp)				



TELEPHONE: 1-888-457-1275 FAX: 1-888-626-2907



PO BOX 66738 #76520, SAINT LOUIS, MO 63166-6738 USA



WEBSITE:

www.AccessDoorsAndPanels.com